

### ES-3-150

System Performance	Metric	American
Rated Sine Force	3 kN	660 lbf
Rated Random Force	3 kN	660 lbf
Rated Shock Force	6 kN	1320 lbf
Usable Frequency	DC-4000 Hz	DC-4000 Hz
Maximum Velocity	2 m/s	78.7 in/s
Maximum Acceleration	1000 m/s <sup>2</sup>	100 g
Maximum Static Payload	120 kg	264 lbs
Resonance Frequency	2900±5% Hz	2900±5% Hz
Maximum Displacement p-p	25 mm	1 in

### Shaker: ET-3-150

Mass of Moving Elements	3 kg	6.6 lbs
Armature Diameter	150 mm	5.9 in
Weight	480 kg	1058 lbs
Body Suspension Natural Frequency	<3 Hz	<3 Hz
Stray Flux Density	<10 Gauss	<10 Gauss
Dimension L×W×H	756×618×660.5 mm	29.8×24.3×26 in

### Power Amplifier: SDA-3

Power	3 kVA	3 kVA
Power Supply Requirement	6.5 kVA	6.5 kVA
Dimension L×W×H	607×820×1593 mm	23.9×32.3×62.7 in
Weight Uncrated	200 kg	441 lbs



### Blower: B-200

Power	0.75 kW	1 hp
Air Flow	0.1 m <sup>3</sup> /s	100 l/s
Air Pressure	1 kPa	0.145 psi
Weight Uncrated	30 kg	66 lbs


### Options

- Magnesium or Aluminum Armature
- Customized Fixtures (T, L, Cube)
- Combo or Standalone Slip Table
- Pneumatic Isolators or Free Foundation Isolation Base
- Motorized Shaker Body Rotation System
- Air Caster or Glide Rail
- Head Expanders and Vertical Support Platforms
- Enclosed Air Inlet and Outlet Ducts
- Thermal barrier
- Remote control


### Outline Drawing



Shaker ET-3-150



Power Amplifier SDA-3



Blower B-200

### Air-cooled Series

The air-cooled series electro-dynamic vibration test system has the advantages, such as wide frequency range, excellent indicators, high reliability, small floor space, easy to move, and easy to operate. At present, this series has a variety of models of vibration generators to choose. The exciting force range is from 1kN to 70kN and maximum load is from 70 kg to 1000 kg. Also, the climate and mechanics environmental testing equipments are provided.

### Performance characteristics

- Sinusoidal excitation force range: 1kN ~ 70kN
- Random to sinusoidal excitation force ratio 1:1
- Two-times-of-sine shock force (Three times optional)
- Displacement peak-to-peak value of 25mm, 40mm, 51mm, 76mm or 100mm
- Lightweight armature with optimization design and strong vibration-resistant performance, and with better vibration isolation effect of air spring at trunnion position
- Strong bearing capacity of air spring in central room, and good low-frequency performance
- Double magnetic circuit design, with low flux leakage and uniform magnetic field
- Sine, Random and Shock etc. test function
- Good cooling effect and low noise fan

NOTE: In keeping with our commitment to continuous product improvement, the information herein is subject to change.