

ES-300-870

System Performance	Metric	American
Rated Sine Force	300 kN	77000 lbf
Rated Random Force	240 kN	55000 lbf
Rated Shock Force	600/900* kN	132000/198000* lbf
Usable Frequency	DC-1700 Hz	DC-2100 Hz
Maximum Velocity	2/2.5* m/s	78.7/98.4* in/s
Maximum Acceleration	1000 m/s ²	100 g
Maximum Static Payload	6000 kg	13227 lbs
Resonance Frequency	1600±5% Hz	1600±5% Hz
Maximum Displacement p-p	51 mm	2 in

Shaker: ET-300-870

Mass of Moving Elements	300 kg	661 lbs
Armature Diameter	870 mm	34.2 in
Weight	About 23000 kg	About 50706 lbs
Body Suspension Natural Frequency	2.5 Hz	2.5 Hz
Stray Flux Density	<10 Gauss	<10 Gauss
Dimension L×W×H	2900×2066×1986 mm	114.2×81.3×78.2 in

Power Amplifier: SDA-380

Power	380 kVA	200 kVA
Power Supply Requirement	520 kVA	520 kVA
Dimension L×W×H	6000×1010×2070mm	236.2×39.8×81.5 in
Weight Uncrated	About 4000 kg	About 8818 lbs


Water Cooling: CU-3

Internal Circle Water Flow (Distilled Water)	120 L/min	26.4 gal/min
Internal Circle Water Pressure (Distilled Water)	1 Mpa	145 psi
External Circle Water Flow (City Water)	320 L/min	70.4 gal/min
External Circle Water Pressure (City Water)	0.25-0.4 Mpa	36-58 psi
Water Pump Power (Internal/External)kW	8/6.5 kW	8/6.5 kW
Distilled Water Requirement	Hardness 30ppm, PH7~8, Conductivity 1Us/cm	
Unit Weight (kg)	About 300 kg	About 661 lbs
Dimension L×W×H	607×1010×2070mm	23.9×39.8×81.5 in

Options

- Magnesium or Aluminum Armature
- Customized Fixtures (T, L, Cube)
- Combo or Standalone Slip Table
- Pneumatic Isolators or Free Foundation Isolation Base
- Motorized Shaker Body Rotation System
- Air Caster or Glide Rail
- Head Expanders and Vertical Support Platforms
- Cooling tower
- Thermal barrier
- Remote control

Outline Drawing



ET-300-870



Power Amplifier SDA-380



Water Cooling CU-3

Water-cooled Series

Water-cooled Vibration test system features with the large force, large bearing capacity and high cooling efficiency, to complete the tri-axial sinusoidal vibration test, broadband random vibration test and classical (semi-sinusoidal, trapezoidal, and postpeak sawtooth) pulse and shock response spectrum test. The multi-environment combined test can be completed with the equipped climate chamber. At present, this series has a variety of models to choose. The exciting force range is from 50 kN to 500 kN and maximum load is from 800 kg to 10000 kg.

Performance characteristics

- Random to sinusoidal excitation force ratio: 1:1
- Two-times-of-sine shock force (Three times optional)
- Displacement peak-to-peak: 51mm, 76mm or 100mm
- Lightweight armature and large working table
- Better vibration isolation effect of air spring at trunnion position
- Large bearing capacity of air spring in central room, and good low-frequency performance
- Equipped with an automatic centering system, to control the armature is always in the balance position during movement
- Double magnetic circuit design, with low flux leakage and uniform magnetic field

NOTE: In keeping with our commitment to continuous product improvement, the information herein is subject to change.